

ABOX-5200

Intel 8th Gen Core i7/i5/i3 CPU w/
10 x GbE (Optional for M12 connector and 8 x PoE total Max. 100W)/ 3 x COM/ 3 x DP/ 4 x USB 3.0/
9-48V Input AI GPU Computing



Features

- Intel 8th Gen Core i7/i5/i3
- 10 x GbE LAN (Optional for M12 connector and 8 x PoE total Max. 100W)
- 8 x GPI, 4 x GPO and 3 x RS-232/422/485
- 3 x Display Ports
- Dual Hot Swappable SATA Storage RAID 0,1,5
- 9-48V DC Input and Operating Temp.: -40~70°C
- TPM 2.0



Taiwan Patent No. M447854



Delay Time



Power Ignition



Wide Range



Wireless



Battery Backup

System	
CPU	Intel Gen8 Core i7-8700T (12M Cache 2.4GHz up to 4.0GHz) Intel Gen8 Core i5-8500T (9M Cache 2.1GHz up to 3.5GHz) Intel Gen8 Core i3-8100T (6M Cache 3.1GHz) Intel Gen8 Celeron G4900T (2M Cache 2.9GHz)
Memory	2 x DDR4 2400 MHz SO-DIMM up to 32GB
LAN Chipset	9 x Intel i210-AT and 1 x i219 (iAMT9.5 w/ i5, i7 only) Gb/s Ethernet Controllers Onboard Support PXE and WOL
Watchdog	1 ~ 255 Level Reset
TPM	2.0
I/O	
Serial Port	3 x RS 232/422/485 (Auto Direction Control)
USB Port	4 x USB 3.0 Ports
LAN	10 x RJ45 Ports for GbE (Optional for M12 connector and 8 x PoE total Max. 100W)
Video Port	3 x DP Ports
DIO Port	8 x GPI and 4 x GPO
Audio	1 x Line-out, 1 x Line-in and 1 x Mic-in
Expansion Bus	3 x Full Mini-PCle Slots and 1x M.2 A-E Key 2230 slot (2 x SIM Card Sockets for 3G/LTE)
Power Requirement	
Power Input	9V - 48V DC Power Input
Power Protection	Automatics Recovery Short Circuit Protection
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery(UPS)	Internal Battery Kit for 10 Mins Operating (optional) Patent No. : M447854 - Build-in Battery
Software	
Operating System	Win 10, Ubuntu 18.04 64bit

Graphics	
Graphics	Intel® UHD Graphics 630
Resolution	Max Resolution (DP) : 4096x2304@60Hz
Storage	
Type	2 x 2.5" Drive Bay for SATA Type HDD/SSD RAID 0, 1, 5 1 x mSATA
Environmental	
Operating Temp.	-40°C ~ 70°C, ambient w/ 0.6m/s airflow
Storage Temp.	-40°C ~ 80°C
Relative Humidity	10% RH – 90% RH (non-condensing)
Vibration (random)	IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD
Vibration Operating	MIL-STD-810G, Method 514.6, Procedure I, Category 4
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Certifications	CE, FCC Class A, E13
Mechanical	
Construction	Aluminum Alloy
Mounting	Wall-mount
Weight	5190g (bare-bone)
Dimensions	260(L) x 250(W) x 95(H) mm
Ordering Information	
Part Number	ABOX-5200P-i7 Optional for i5/i3/C1 (with PoE) ABOX-5200-i7 Optional for i5/i3/C1
Description	Intel 8th Gen Core i7/i5/i3 CPU w/ 10 x GbE/ 3 x COM/ 3 x DP/ 4 x USB 3.0/ 9-48V Input AI GPU Computing
State of Origin	Made in Taiwan